

KERN 440-21A

Der Klassiker im Labor

KERN®



Measuring system

Adjustment options:	External calibration
Linearity:	3 mg
Readout [d]:	1 mg
Recommended adjusting weight:	50 g (F2)
Reproducibility:	1 mg
Resolution:	60000
Stabilisation time:	3 s
Warm up time:	2 h
Weighing range [Max]:	60 g
Weighing system:	Strain gauge
Weighing units:	ct dwt g gn mo oz oz t l (HK) tl (Tw) tol

Display

Display digit height:	1,500 cm
-----------------------	----------

Technical data about verification

n/a:	2 g
------	-----

Counting

Counting resolution:	30000
Minimum piece weight at piece counting:	2 mg

Functions

Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time:	12 h
Operating time (Backlight off):	20 h
Rechargeable battery:	Rchrg. battery optional

Service

DAkkS Certificate:	963-127
--------------------	---------

Category

Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	340 x 210 x 170 mm
Gross weight:	1,340 kg
Net weight:	930 g
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions draft shield (dxH):	106 42
Dimensions housing (WÄDÄH):	165 x 230 x 80 mm
Material weighing plate:	Plastic
Weighing space (dxH):	90 40
Weighing surface (d):	81