

KERN 572-55



Allrounder z. B. als Präzisionswaage im Labor oder im rauen Industrieinsatz, auch mit Eichzulassung [M]



Functions

Conversion function:	yes
Counting function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Suspended weighing:	Loop
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

Power supply

Charging time:	10 h
Input voltage:	100 V - 240 V
Operating time (Backlight off):	50 h
Operating time (Backlight on):	25 h
Rechargeable battery:	Rchrg. battery optional

Service

DAkkS Certificate:	963-128
--------------------	---------

Category

Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	400 x 340 x 220 mm
Gross weight:	4,400 kg
Net weight:	2,700 kg
Shipping method:	Parcel service

Construction

Casing material:	Cast aluminium alloys
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (WxD):	160 x 200 mm

Measuring system

Adjustment options:	External calibration
Linearity:	150 mg
Readout [d]:	50 mg
Recommended adjusting weight:	20000 g (F1)
Reproducibility:	100 mg
Resolution:	400000
Stabilisation time:	3 s
Warm up time:	4 h
Weighing range [Max]:	20 kg
Weighing system:	Strain gauge
Weighing units:	ct dwt g gn kg lb mo oz ozt t tl (Cn) tl (HK) tl (Singap. Malays) tl (Tw) to

Display

Display digit height:	1,800 cm
-----------------------	----------

Technical data about verification

n/a:	200 g
------	-------

Counting

Counting resolution:	400000
Minimum piece weight at piece counting:	50 mg