

KERN BAN600K-1SM



Edelstahl-Bodenwaage mit komplettem Staub- und Spritzwasserschutz IP68, XL-Wägebrücke und Eichzulassung [M]



Weighing with tolerance range: yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply

Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service

DAkkS Certificate:	963-130
Verification:	965-230

Category

Category:	Balances
Product Group:	Industrial scale

Packaging & shipping

Delivery:	120 h
Dimensions packaging (WxDxH):	1050 x 1050 x 350 mm
Gross weight:	106 kg
Net weight:	97 kg
Shipping method:	Freight forwarder

Construction

Cable length of display device:	5 m
Dimensions of display device (WxDxH):	232 x 170 x 80 mm
Dimensions of weighing plate (WxDxH):	1000 x 1000 x 80 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	1000 x 1000 x 80 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1000 x 1000 mm

Measuring system

Adjustment options:	External calibration
Linearity:	200 g
Readout [d]:	200 g
Recommended adjusting weight:	600 kg (M2)
Reproducibility:	200 g
Resolution:	3000
Stabilisation time:	2 s
Warm up time:	10 min
Weighing range [Max]:	600 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height:	5,500 cm
-----------------------	----------

Technical data about verification

Minimum load [Min]:	4 kg
Periodic Verification Italy:	969-112
Verification approval conforming to 90/384/EEC:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	200 g

Functions

Counting function:	yes
Data hold function:	yes
Function to save totals:	yes
PRE-TARE function:	yes
Vibration-free weighing (Animal weighing program):	yes