KERN BKN1T-4M



Stainless steel floor scale with folding weighing plate and complete dust and spray protection to IP68 and EC type approval [M]



Measuring system	
Adjustment options:	External calibration
Linearity:	1,500 kg
Measuring range [Max]:	40 °C
Readout [d]:	500 g
Recommended adjusting weight:	1500 kg (M2)
Reproducibility:	500 g
Resolution:	3000
Stabilisation time:	2 s
Warm up time:	10 min
Weighing range [Max]:	1,500 t
Weighing system:	Strain gauge
Weighing units:	kg

Display	
Display digit height:	5,500 cm

Technical data about verification	
Minimum load [Min]:	10 kg
Periodic Verification for Italy:	969-112
Verification approval conforming to 2014/31/EU:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 g

Functions			
Counting function:	yes		
Data hold function:	yes		
Function to save totals:	yes		
PRE-TARE function:	yes		
Vibration-free weighing (Animal weighing program):	yes		
Weighing with tolerance range:	yes		
KEDNIO COLINI Omebili. Zinamalai 4	70000 D - I'	^	T . 1

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply	
Charging time:	12 h
Input voltage:	220 V - 240 V AC 50 Hz
n/a:	CH EURO
Operating time (Backlight off):	80 h
Operating time (Backlight on):	40 h
Rechargeable battery:	Rchrg. battery optional (factory)

Service	
Adjustment at the location of installation: 961-2	50

DAkkS Certificate: 963-130 Verification: 965-230

Category	
Brand:	KERN
Category:	Balances

120 h
1550 x 1300 x 350 mm
156 kg
126 kg
Freight forwarder
1

Construction	
Cable length of display device:	5 m
Casing material:	stainless steel
Dimensions of display device (WxDxH):	232 x 170 x 80 mm
Dimensions of weighing plate (WxDxH):	1500 x 1250 x 110 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	1250 x 1500 x 110 mm
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	1500 x 1250 mm