

KERN CH15K20

Praktisch, preiswert und stets griffbereit

KERN[®]



Functions

| | |
|--|-----|
| Data hold function: | yes |
| Vibration-free weighing (Animal weighing program): | yes |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |

Power supply

| | |
|-----------------|------|
| Operating time: | 20 h |
|-----------------|------|

Service

| | |
|--------------------|----------|
| DAkkS Certificate: | 963-128H |
|--------------------|----------|

Category

| | |
|----------------|---------------|
| Category: | Balances |
| Product Group: | Hanging scale |

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 153 x 230 x 73 mm |
| Gross weight: | 544 g |
| Net weight: | 316 g |
| Shipping method: | Parcel service |

Construction

| | |
|-------------------------------------|------------------|
| Casing material: | Plastic |
| Dimensions housing (WÄDÄH): | 90 x 30 x 175 mm |
| Overall dimensions mounted (WxDxH): | 90 x 30 x 270 mm |

Measuring system

| | |
|-------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 40 g |
| Precision (of [Max]): | 0,005 |
| Readout [d]: | 20 g |
| Recommended adjusting weight: | 10000 g (M3) |
| Reproducibility: | 20 g |
| Resolution: | 750 |
| Stabilisation time: | 2 s |
| Warm up time: | 10 min |
| Weighing range [Max]: | 15 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg lb N |

Display

| | |
|-----------------------|----------|
| Display digit height: | 1,100 cm |
|-----------------------|----------|