

KERN CKE 16K0.1

Selbsterklärende Zählwaage mit Laborgenauigkeit, Zählauflösung bis zu 360.000 Punkte



Power supply

| | |
|---------------------------------|-------------------------|
| Charging time: | 10 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| Operating time: | 40 h |
| Operating time (Backlight off): | 50 h |
| Operating time (Backlight on): | 25 h |
| Rechargeable battery: | Rchrg. battery optional |

Service

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
|--------------------|---------|

Category

| | |
|----------------|----------------|
| Category: | Balances |
| Product Group: | Counting scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 470 x 470 x 190 mm |
| Gross weight: | 7,600 kg |
| Net weight: | 6,500 kg |
| Shipping method: | Parcel service |

Construction

| | |
|-----------------------------|--------------------|
| Dimensions housing (WÄDÄH): | 350 x 390 x 120 mm |
| Material weighing plate: | stainless steel |
| Weighing surface (WxD): | 340 x 240 mm |

Measuring system

| | |
|-------------------------------|---------------------------|
| Adjustment options: | External calibration |
| Linearity: | 300 mg |
| Readout [d]: | 100 mg |
| Recommended adjusting weight: | 10000 g (F1); 5000 g (F1) |
| Reproducibility: | 100 mg |
| Resolution: | 160000 |
| Stabilisation time: | 3 s |
| Warm up time: | 2 h |
| Weighing range [Max]: | 16 kg |
| Weighing system: | Strain gauge |
| Weighing units: | g |

Display

| | |
|-----------------------|----------|
| Display digit height: | 1,800 cm |
|-----------------------|----------|

Counting

| | |
|---|--------|
| Counting resolution: | 160000 |
| Minimum piece weight at piece counting: | 100 mg |

Functions

| | |
|----------------------|------|
| Conversion function: | yes |
| Counting function: | yes |
| PRE-TARE function: | yes |
| Suspended weighing: | Hook |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | 10 °C |