

# KERN DE 35K5DL

Langjähriges Erfolgsmodell mit staub- und spritzwassergeschütztem Auswertegerät



Measuring system	
Adjustment options:	External calibration
Linearity:	15 g   30 g
Readout [d]:	5 g   10 g
Recommended adjusting weight:	30000 g (M1)
Reproducibility:	5 g   10 g
Resolution:	3 3.500
Stabilisation time:	2,500 s
Warm up time:	10 min   10 min
Weighing range [Max]:	15 kg   35 kg
Weighing system:	Strain gauge
Weighing units:	dwt g kg lb mo oz ozt tl (HK) tl (Tw) tol

Display	
Display digit height:	2,500 cm

Counting	
Counting resolution:	3500
Minimum piece weight at piece counting:	10 g

Functions	
Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply	
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time:	12 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service	
DAkkS Certificate:	963-128

Category	
Category:	Balances
Product Group:	Platform scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	620 x 600 x 190 mm
Gross weight:	17,800 kg
Net weight:	15,600 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	1,400 m
Dimensions of display device (WÄDÄH):	225 x 110 x 45 mm
Dimensions of weighing plate (WxDxH):	522 x 403 x 90 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	522 x 403 mm