

# KERN DE60K1D

Langjähriges Erfolgsmodell mit staub- und spritzwassergeschütztem Auswertegerät



Measuring system	
Adjustment options:	External calibration
Linearity:	4 g   8 g
Readout [d]:	1 g   2 g
Recommended adjusting weight:	60 kg (F2)
Reproducibility:	1 g   2 g
Resolution:	30 30.000
Stabilisation time:	2,500 s
Warm up time:	2 h   2 h
Weighing range [Max]:	30 kg   60 kg
Weighing system:	Strain gauge
Weighing units:	dwt g kg lb mo oz ozt tl (HK) tl (Tw) tol

Display	
Display digit height:	2,500 cm

Counting	
Counting resolution:	30000
Minimum piece weight at piece counting:	2 g

Functions	
Counting function:	yes
Percentage determination:	yes
Vibration-free weighing (Animal weighing program):	yes

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply	
Charging time:	10 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time:	12 h
Operating time (Backlight off):	30 h
Operating time (Backlight on):	15 h
Rechargeable battery:	Rchrg. battery optional

Service	
DAkkS Certificate:	963-129

Category	
Category:	Balances
Product Group:	Platform scale

Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	530 x 417 x 160 mm
Gross weight:	7,800 kg
Net weight:	6,700 kg
Shipping method:	Parcel service

Construction	
Cable length of display device:	1,470 m
Dimensions of display device (WÄDÄH):	225 x 110 x 55 mm
Dimensions of weighing plate (WxDxH):	318 x 308 x 80 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	318 x 308 mm