

KERN ECE50K20

Unkompliziert, mobil und preiswert



Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	370 x 330 x 85 mm
Gross weight:	1,730 kg
Net weight:	1,460 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions housing (WÄDÄH):	300 x 325 x 60 mm
Material weighing plate:	Plastic
Weighing surface (WxD):	320 x 260 mm

Measuring system

Adjustment options:	External calibration
Linearity:	80 g
Readout [d]:	20 g
Recommended adjusting weight:	20000 g (M3)
Reproducibility:	20 g
Resolution:	2500
Stabilisation time:	2 s
Tare range:	50 kg
Warm up time:	10 min
Weighing range [Max]:	50 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height:	1,400 cm
-----------------------	----------

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Charging time:	10 h
Operating time:	100 h
Operating time (Backlight off):	30 h
Rechargeable battery:	Rchrg. battery optional

Service

DAkkS Certificate:	963-128
--------------------	---------

Category

Category:	Balances
Product Group:	Bench scale