KERN EOC10K-3A



All-round parcel scale with practical Flip/Flop display device for greatest ease of use



Measuring system	
Adjustment options:	External calibration
Linearity:	3 g
Readout [d]:	1 g
Recommended adjusting weight:	12 kg (F2)
Reproducibility:	1 g
Resolution:	12000
Stabilisation time:	3 s
Tare range:	-12000000 mg
Warm up time:	30 min
Weighing range [Max]:	12 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height:

Counting

Counting resolution:	24000
Mininum piece weight at piece counting (Laboratory:	500 mg
Mininum piece weight at piece counting (Normal):	5 g

2,400 cm

Functions

Counting function:	yes	
Function to save totals:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	12 h
Input voltage:	100V-240V 0.4A
n/a:	CH EURO UK US
n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional -
	intern
Service	
Adjustment at the location of installation	on: 961-248
DAkkS Certificate:	963-128
Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale
Packaging & shipping	
Delivery:	24 h
Delivery: Dimensions packaging (WxDxH):	24 h 715 x 355 x 180 mm
•	
Dimensions packaging (WxDxH):	715 x 355 x 180 mm
Dimensions packaging (WxDxH): Gross weight:	715 x 355 x 180 mm 7,500 kg
Dimensions packaging (WxDxH): Gross weight: Net weight:	715 x 355 x 180 mm 7,500 kg 6,500 kg
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	715 x 355 x 180 mm 7,500 kg 6,500 kg
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel
Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate: Revolving screw feet:	715 x 355 x 180 mm 7,500 kg 6,500 kg Parcel service 3 m 268 x 115 x 80 mm 300 x 300 x 110 mm 33 cm yes stainless steel yes