KERN EOC30K-3L







| Measuring system | |
|-------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 15 g 30 g |
| Readout [d]: | 5 g 10 g |
| Recommended adjusting weight: | 30 kg (M1) |
| Reproducibility: | 5 g 10 g |
| Resolution: | 3 3.500 |
| Stabilisation time: | 2 s |
| Tare range: | -30000000 mg |
| Warm up time: | 10 min 10 min |
| Weighing range [Max]: | 15 kg 35 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

| Display | | |
|-----------------------|----------|--|
| Display digit height: | 2,400 cm | |

| Counting | |
|---|-------|
| Counting resolution: | 35000 |
| Mininum piece weight at piece counting (Laboratory: | 1 g |
| Mininum piece weight at piece counting (Normal): | 10 g |

| Functions | | |
|--|-----|--|
| Counting function: | yes | |
| Function to save totals: | yes | |
| Percentage determination: | yes | |
| Vibration-free weighing (Animal weighing program): | yes | |
| Weighing with tolerance range: | yes | |

| Environmental conditions | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

| Power supply | |
|----------------|----------------|
| Charging time: | 12 h |
| Input voltage: | 100V-240V 0.4A |
| n/a: | CH EURO UK US |

| n/a: | Mains adapter external |
|---------------------------------|--------------------------|
| Power supply | |
| Operating time (Backlight off): | 35 h |
| Operating time (Backlight on): | 8 h |
| Rechargeable battery: | Pohra hattery ontional - |

| Rechargeable battery: | Ronrg. battery optional - | |
|-----------------------|---------------------------|--|
| | intern | |
| | | |

Adjustment at the location of installation: 961-248

Service

| DAkkS Certificate: | 963-128 |
|--------------------|------------------|
| Category | |
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Industiral scale |

| Packaging & shipping | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 870 x 480 x 150 mm |
| Gross weight: | 12,500 kg |
| Net weight: | 9 kg |
| Shipping method: | Parcel service |

| Construction | |
|---------------------------------------|--------------------|
| Cable length of display device: | 3 m |
| Dimensions of display device (WxDxH): | 268 x 115 x 80 mm |
| Dimensions of weighing plate (WxDxH): | 500 x 400 x 120 mm |
| of stand: | 33 cm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 500 x 400 mm |