KERN EOC60K-2L



All-round parcel scale with practical Flip/Flop display device for greatest ease of use



Measuring system	
Adjustment options:	External calibration
Linearity:	30 g 60 g
Readout [d]:	10 g 20 g
Recommended adjusting weight:	60 kg (M1)
Reproducibility:	10 g 20 g
Resolution:	3 3.000
Stabilisation time:	2 s
Tare range:	-60000000 mg
Warm up time:	10 min 10 min
Weighing range [Max]:	30 kg 60 kg
Weighing system:	Strain gauge
Weighing units:	kg
Display	
Display digit height:	2,400 cm

\sim	~		n	41	n	~
	υ	u	u.	U		Ч

Counting resolution:	30000	
Mininum piece weight at piece counting (Laboratory:	2 g	
Mininum piece weight at piece counting (Normal):	20 g	

Functions

Counting function:	yes	
Function to save totals:	yes	
Percentage determination:	yes	
Vibration-free weighing (Animal weighing program):	yes	
Weighing with tolerance range:	yes	

Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %
Power supply	
Charging time:	12 h
Input voltage:	100V-240V 0.4A
n/a:	CH EURO UK US
n/a:	Mains adapter external
Power supply	
Operating time (Backlight off):	35 h
Operating time (Backlight on):	8 h
Rechargeable battery:	Rchrg. battery optional -
	intern
Service	
Adjustment at the location of installation	:961-249
DAkkS Certificate:	963-129
Category	
Brand:	KERN
Category:	Balances
Product Group:	Industiral scale
Packaging & shipping	
Delivery:	24 h
Dimensions packaging (WxDxH):	870 x 480 x 150 mm
Gross weight:	12,500 kg
Maturalalati	
Net weight:	9 kg
Shipping method:	9 kg Parcel service
•	•
Shipping method:	•
Shipping method: Construction	Parcel service
Shipping method: Construction Cable length of display device: Dimensions of display device	Parcel service 3 m
Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate	Parcel service 3 m 268 x 115 x 80 mm
Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH):	Parcel service 3 m 268 x 115 x 80 mm 500 x 400 x 120 mm
Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand:	Parcel service 3 m 268 x 115 x 80 mm 500 x 400 x 120 mm 33 cm
Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator:	Parcel service 3 m 268 x 115 x 80 mm 500 x 400 x 120 mm 33 cm yes
Shipping method: Construction Cable length of display device: Dimensions of display device (WxDxH): Dimensions of weighing plate (WxDxH): of stand: Level indicator: Material weighing plate:	Parcel service 3 m 268 x 115 x 80 mm 500 x 400 x 120 mm 33 cm yes stainless steel