

# KERN FKTF3K0.5LM



Kontrollwaage mit Touchscreen-Bedienung zur Stichprobenprüfung nach der eichamtlichen Fertigpackungsverordnung (FPVO) und zur Füllmengensteuerung im Produktionsprozess



## Functions

Capacity display:	yes
Conversion function:	yes
PRE-TARE function:	yes
SLEEP function:	yes
Standby function:	yes
Suspended weighing:	Hook
Time display:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

## Power supply

Charging time:	10 h
Input voltage:	100 V - 240 V
Operating time:	15 h
Operating time (Backlight off):	20 h
Operating time (Backlight on):	10 h

## Service

DAkkS Certificate:	963-127
Verification:	965-227

## Category

Category:	Balances
-----------	----------

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	465 x 470 x 190 mm
Gross weight:	7,600 kg
Net weight:	6,370 kg
Shipping method:	Parcel service

## Construction

Dimensions housing (WÄDÄH):	350 x 390 x 120 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Weighing surface (WxD):	340 x 240 mm

## Measuring system

Adjustment options:	External calibration
Linearity:	500 mg
Readout [d]:	500 mg
Recommended adjusting weight:	3000 g (F1)
Reproducibility:	500 mg
Resolution:	6000
Stabilisation time:	3 s
Tare range:	3 kg
Warm up time:	30 min
Weighing range [Max]:	3 kg
Weighing system:	Strain gauge
Weighing units:	g kg

## Display

Display digit height:	1,800 cm
Display digit height:	4 mm

## Technical data about verification

Minimum load [Min]:	10 g
Periodic Verification Italy:	969-112
Verification approval conforming to 90/384/EEC:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	500 mg