

# KERN FKT65K0.2L

Touchscreen-Industriewaage mit riesigem Funktionsumfang, auch mit Eichzulassung [M]



## Functions

Conversion function:	yes
Counting function:	yes
Dispensing function:	yes
Function to save totals:	yes
Percentage determination:	yes
PRE-TARE function:	yes
SLEEP function:	yes
Standby function:	yes
Statistical function:	yes
Suspended weighing:	Hook
Time display:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C

## Power supply

Charging time:	10 h
Input voltage:	100 V - 240 V
Operating time:	20 h
Operating time (Backlight off):	20 h
Operating time (Backlight on):	10 h
Rechargeable battery:	Rchrg. battery optional - intern

## Service

DAkkS Certificate:	963-129
--------------------	---------

## Category

Category:	Balances
Product Group:	Bench scale

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	470 x 470 x 190 mm
Gross weight:	7,600 kg
Net weight:	6,500 kg
Shipping method:	Parcel service

## Measuring system

Adjustment options:	External calibration
Linearity:	1 g
Readout [d]:	200 mg
Recommended adjusting weight:	50000 g (E2); 10000 g (E2)
Reproducibility:	400 mg
Resolution:	325000
Stabilisation time:	3 s
Warm up time:	2 h
Weighing range [Max]:	65 kg
Weighing system:	Strain gauge
Weighing units:	* ct dwt g kg lb mo oz ozt t tl (HK) tl (Singap. Malays) tl (Tw)

## Display

Display digit height:	1,800 cm
Display digit height:	4 mm

## Counting

Counting resolution:	325000
Minimum piece weight at piece counting:	200 mg
Reference weight:	yes

# KERN FKT65K0.2L



Touchscreen-Industriewaage mit riesigem Funktionsumfang, auch mit Eichzulassung [M]

## Construction

Dimensions housing (WÄDÄH): 350 x 390 x 120 mm

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes

Weighing surface (WxD): 340 x 240 mm