

KERN FKT6K0.02L



Touchscreen-Industriewaage mit riesigem Funktionsumfang, auch mit Eichzulassung [M]



Functions

| | |
|--|------|
| Conversion function: | yes |
| Counting function: | yes |
| Dispensing function: | yes |
| Function to save totals: | yes |
| Percentage determination: | yes |
| PRE-TARE function: | yes |
| SLEEP function: | yes |
| Standby function: | yes |
| Statistical function: | yes |
| Suspended weighing: | Hook |
| Time display: | yes |
| Vibration-free weighing (Animal weighing program): | yes |
| Weighing with tolerance range: | yes |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | 10 °C |

Power supply

| | |
|---------------------------------|----------------------------------|
| Charging time: | 10 h |
| Input voltage: | 100 V - 240 V |
| Operating time: | 20 h |
| Operating time (Backlight off): | 20 h |
| Operating time (Backlight on): | 10 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
|--------------------|---------|

Category

| | |
|----------------|-------------|
| Category: | Balances |
| Product Group: | Bench scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 470 x 470 x 190 mm |
| Gross weight: | 7,600 kg |
| Net weight: | 6,500 kg |
| Shipping method: | Parcel service |

Measuring system

| | |
|-------------------------------|--|
| Adjustment options: | External calibration |
| Linearity: | 100 mg |
| Readout [d]: | 20 mg |
| Recommended adjusting weight: | 5000 g (F1); 1000 g (F1) |
| Reproducibility: | 40 mg |
| Resolution: | 300000 |
| Stabilisation time: | 3 s |
| Warm up time: | 2 h |
| Weighing range [Max]: | 6 kg |
| Weighing system: | Strain gauge |
| Weighing units: | * ct dwt g kg lb mo oz ozt t tl (HK) tl (Singap. Malays) tl (Tw) |

Display

| | |
|-----------------------|----------|
| Display digit height: | 1,800 cm |
| Display digit height: | 4 mm |

Counting

| | |
|---|--------|
| Counting resolution: | 300000 |
| Minimum piece weight at piece counting: | 20 mg |
| Reference weight: | yes |

KERN FKT6K0.02L



Touchscreen-Industriewaage mit riesigem Funktionsumfang, auch mit Eichzulassung [M]

Construction

Dimensions housing (WÄDÄH): 350 x 390 x 120 mm

Level indicator: yes

Material weighing plate: stainless steel

Revolving screw feet: yes

Weighing surface (WxD): 340 x 240 mm