

# KERN HFT10T2

Robuste Industrie-Kranwaage bis 15 t mit Funk-Auswertegerät und Datenschnittstelle RS-232 zur Übertragung der Wäageergebnisse



## Measuring system

Adjustment options:	External calibration
Linearity:	4 kg
Precision (of [Max]):	0,002
Readout [d]:	2 kg
Recommended adjusting weight:	10000 kg (M3)
Reproducibility:	2 kg
Resolution:	5000
Stabilisation time:	2 s
Tare range:	-10000000000 mg
Warm up time:	10 min
Weighing range [Max]:	10 t
Weighing system:	Strain gauge
Weighing units:	kg

## Display

Display digit height:	2,200 cm
-----------------------	----------

## Functions

Data hold function:	yes
Function to save totals:	yes
Peak function:	yes
Time display:	yes
Vibration-free weighing (Animal weighing program):	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	0 °C
Minimum humidity:	0 %

## Power supply

Charging time:	8 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time (Backlight off):	80 h

## Service

DAkkS Certificate:	963-133H
ISO calibration certificate:	961-106

## Category

Category:	Balances
Product Group:	Crane scale

# KERN HFT10T2



Robuste Industrie-Kranwaage bis 15 t mit Funk-Auswertegerät und Datenschnittstelle RS-232 zur Übertragung der Wäageergebnisse

## Packaging & shipping

Delivery:	48 h
Dimensions packaging (WxDxH):	800 x 400 x 470 mm
Gross weight:	48 kg
Net weight:	42 kg
Shipping method:	Freight forwarder

## Construction

Dimensions housing (WÄDÄH):	175 x 50 x 85 mm
Dimensions of display device (WÄDÄH):	175 x 50 x 85 mm
Overall dimensions mounted (WxDxH):	180 x 870 x 180 mm