

KERN IEX10K-3MUK



Plattformwaage mit ATEX-Zulassung in der Explosionsklasse II B, mit Eichzulassung [M]
(Netzadapter UK)



Counting

Counting resolution:	3000
Minimum piece weight at piece counting:	5 g

Functions

Counting function:	yes
Peak function:	yes
PRE-TARE function:	yes
Weighing with tolerance range:	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	-10 °C
Minimum humidity:	0 %

Power supply

Input voltage:	230V 50Hz; Ex model ZRI02-II (2) G(Ex Ib) IIC
----------------	--

Service

DAkkS Certificate:	963-128
Verification:	965-228

Category

Category:	Balances
Product Group:	Industrial scale

Packaging & shipping

Delivery:	504 h
Dimensions packaging (WxDxH):	550 x 420 x 220 mm
Gross weight:	9 kg
Net weight:	9,500 kg
Shipping method:	Parcel service

Construction

Cable length of display device:	2,500 m
Dimensions of display device (WÄDÄH):	170 x 172 x 76 mm
Dimensions of weighing plate (WxDxH):	300 x 300 x 70 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Revolving screw feet:	yes
Wall mount:	yes
Weighing surface (WxD):	300 x 300 mm

Measuring system

Adjustment options:	External calibration
Linearity:	5 g
Readout [d]:	5 g
Recommended adjusting weight:	15000 g (M1)
Reproducibility:	5 g
Resolution:	3000
Stabilisation time:	2 s
Tare range:	-15000000 mg
Warm up time:	10 min
Weighing range [Max]:	15 kg
Weighing system:	Strain gauge
Weighing units:	kg

Display

Display digit height:	1,800 cm
-----------------------	----------

Technical data about verification

Minimum load [Min]:	100 g
Periodic Verification Italy:	969-112
Verification approval conforming to 90/384/EEC:	yes
Verification by KERN possible:	yes
Verification class:	III
Verification value [e]:	5 g