

KERN IFS10K-4

Industriezählwaage mit komfortabler Zehnertastatur zur bequemen Dateneingabe, Zählauflösung 75000 Punkte



Measuring system

| | |
|-------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 400 mg 800 mg |
| Readout [d]: | 100 mg 200 mg |
| Recommended adjusting weight: | 15000 g (F2) |
| Reproducibility: | 100 mg 200 mg |
| Resolution: | 60 75.000 |
| Stabilisation time: | 3 s |
| Tare range: | 15 kg |
| Warm up time: | 2 h 2 h |
| Weighing range [Max]: | 6 kg 15 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

Display

| | |
|-----------------------|----------|
| Display digit height: | 1,650 cm |
| Display digit height: | 1,300 cm |

Counting

| | |
|---|--------|
| Counting resolution: | 75000 |
| Minimum piece weight at piece counting: | 200 mg |
| Reference weight: | yes |

Functions

| | |
|--------------------------------|-----|
| Counting function: | yes |
| Function to save totals: | yes |
| Peak function: | yes |
| Percentage determination: | yes |
| Weighing with tolerance range: | yes |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | 0 °C |

Power supply

| | |
|---------------------------------|-----------------------------------|
| Charging time: | 12 h |
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Operating time (Backlight off): | 40 h |
| Operating time (Backlight on): | 30 h |
| Rechargeable battery: | Rchrg. battery optional (factory) |

Service

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
|--------------------|---------|

Category

| | |
|----------------|------------------|
| Category: | Balances |
| Product Group: | Industrial scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 690 x 412 x 225 mm |
| Gross weight: | 7,060 kg |
| Net weight: | 5,350 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------------------------------|--------------------|
| Cable length of display device: | 3 m |
| Casing material: | Plastic |
| Dimensions of display device (WÄDÄH): | 260 x 150 x 65 mm |
| Dimensions of weighing plate (WxDxH): | 300 x 240 x 110 mm |
| of stand: | 33 cm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 460 x 240 x 360 mm |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 300 x 240 mm |