

KERN IXS100K-3L



Plattformwaage mit Edelstahl-IP68-Auswertegerät, XL-Display und Eichzulassung [M] â auch als hochauflösende Variante mit Feinanzeige



Measuring system

| | |
|-------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 15 g |
| Readout [d]: | 5 g |
| Recommended adjusting weight: | 150 kg (M1) |
| Reproducibility: | 5 g |
| Resolution: | 30000 |
| Stabilisation time: | 2 s |
| Tare range: | -150000000 mg |
| Warm up time: | 2 h |
| Weighing range [Max]: | 150 kg |
| Weighing system: | Strain gauge |
| Weighing units: | kg |

Display

| | |
|-----------------------|----------|
| Display digit height: | 5,500 cm |
|-----------------------|----------|

Counting

| | |
|---|-------|
| Counting resolution: | 30000 |
| Minimum piece weight at piece counting: | 5 g |

Functions

| | |
|--------------------------------|-----|
| Counting function: | yes |
| Data hold function: | yes |
| Function to save totals: | yes |
| Help function on the display: | yes |
| Peak function: | yes |
| PRE-TARE function: | yes |
| Weighing with tolerance range: | yes |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

Power supply

| | |
|---------------------------------|-----------------------------------|
| Charging time: | 12 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| Operating time (Backlight off): | 80 h |
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional (factory) |

Service

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-129 |
|--------------------|---------|

Category

| | |
|----------------|------------------|
| Category: | Balances |
| Product Group: | Industrial scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 590 x 925 x 245 mm |
| Gross weight: | 38 kg |
| Net weight: | 35 kg |
| Shipping method: | Parcel service |

Construction

| | |
|---------------------------------------|----------------------|
| Cable length of display device: | 2,500 m |
| Dimensions of display device (WÄDÄH): | 232 x 170 x 80 mm |
| Dimensions of weighing plate (WxDxH): | 650 x 500 x 133,5 mm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Revolving screw feet: | yes |
| Wall mount: | yes |
| Weighing surface (WxD): | 650 x 500 mm |