

KERN KDE-T

Multifunktionsmodell, geschützt durch IP65



Category

| | |
|----------------|-----------------|
| Category: | Display devices |
| Product Group: | Display device |

Packaging & shipping

| | |
|-------------------------------|-------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 205 x 270 x 70 mm |
| Gross weight: | 1 kg |
| Net weight: | 700 g |
| Shipping method: | Parcel service |

Construction

| | |
|-----------------------------|-------------------|
| Dimensions housing (WÄDÄH): | 225 x 110 x 45 mm |
|-----------------------------|-------------------|

Measuring system

| | |
|------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearisation (points): | 4 |
| Number of weighing ranges: | 2 |
| Resolution (non verifiable): | 20000 |
| Weighing units: | g kg lb oz |

Display

| | |
|-----------------------|----------|
| Display digit height: | 2,500 cm |
|-----------------------|----------|

Functions

| | |
|--|-----|
| Counting function: | yes |
| Data hold function: | yes |
| Percentage determination: | yes |
| PRE-TARE function: | yes |
| Time display: | yes |
| Vibration-free weighing (Animal weighing program): | yes |

Environmental conditions

| | |
|--------------------------------|-------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 35 °C |
| Minimum ambient temperature: | 5 °C |

Power supply

| | |
|---------------------------------|----------------------------------|
| Charging time: | 10 h |
| Input voltage: | 100 V - 240 V 50 / 60 Hz |
| Operating time: | 24 h |
| Operating time (Backlight off): | 15 h |
| Operating time (Backlight on): | 10 h |
| Rechargeable battery: | Rchrg. battery optional - intern |