

# KERN PCB 6000-1

Der Standard im Labor



## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

## Power supply

Charging time:	8 h
Input voltage:	220 V - 240 V AC 50 Hz
Operating time:	12 h
Operating time (Backlight off):	48 h
Operating time (Backlight on):	24 h
Rechargeable battery:	Rechrg. battery optional

## Service

DAkkS Certificate:	963-128
--------------------	---------

## Category

Category:	Balances
Product Group:	Precision balance

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	230 x 335 x 175 mm
Gross weight:	2,150 kg
Net weight:	1,650 kg
Shipping method:	Parcel service

## Construction

Casing material:	Plastic
Dimensions housing (WĀDĀH):	245 x 167 x 82 mm
Material weighing plate:	stainless steel
Weighing surface (WxD):	153 x 173 mm

## Measuring system

Adjustment options:	External calibration
Linearity:	300 mg
Readout [d]:	100 mg
Recommended adjusting weight:	5000 g (F2)
Reproducibility:	100 mg
Resolution:	60000
Stabilisation time:	3 s
Warm up time:	2 h
Weighing range [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	dwt g kg lb mo oz ozt tl (HK) tl (Tw) tol

## Display

Display digit height:	1,500 cm
-----------------------	----------

## Technical data about verification

n/a:	200 g
------	-------

## Counting

Counting resolution:	30000
Minimum piece weight at piece counting:	200 mg

## Functions

Counting function:	yes
Percentage determination:	yes
Suspended weighing:	Hook
Vibration-free weighing (Animal weighing program):	yes