

# KERN PFB 6000-0M

Schnellanzeigende Präzisionswaage mit komfortabler Bedienphilosophie und Eichzulassung [M]



## Measuring system

Adjustment options:	External calibration
Linearity:	1 g
Readout [d]:	1 g
Recommended adjusting weight:	6000 g (F1)
Reproducibility:	1 g
Resolution:	6000
Stabilisation time:	3 s
Tare range:	5,999 g
Warm up time:	30 min
Weighing range [Max]:	6 kg
Weighing system:	Strain gauge
Weighing units:	g

## Display

Additional Display possible:	no
Display digit height:	1,500 cm
Display digit height:	5 mm

## Technical data about verification

Minimum load [Min]:	50 g
n/a:	2 kg
Verification approval conforming to 90/384/EEC:	yes
Verification by KERN possible:	yes
Verification class:	II
Verification value [e]:	1 g

## Counting

Counting resolution:	30000
Minimum piece weight at piece counting:	200 mg

## Functions

Capacity display:	yes
Counting function:	yes
Percentage determination:	yes

## Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C
Minimum humidity:	0 %

## Power supply

Input voltage:	220 V - 240 V AC 50 Hz
----------------	------------------------

## Service

DAkkS Certificate:	963-128
Verification:	965-217

## Category

Category:	Balances
Product Group:	Precision balance

## Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	330 x 255 x 325 mm
Gross weight:	2,850 kg
Net weight:	1,900 kg
Shipping method:	Parcel service

## Construction

Casing material:	Plastic
Dimensions housing (WÄDÄH):	200 x 190 x 87 mm
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	200 x 190 x 87 mm
Revolving screw feet:	yes
Weighing surface (WxD):	155 x 145 mm