

KERN PLJ1200-3A



Präzisionswaage mit komfortabler Bedienphilosophie, jetzt auch als Milligramm-Waage mit mit enormem Wägebereich bis 2100 g!



Functions

Counting function:	yes
Density determination function:	yes
Peak function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Standby function:	yes
Suspended weighing:	Loop
Weighing with tolerance range:	yes

Environmental conditions

Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5 °C

Power supply

Input voltage:	220 V - 240 V AC 50 Hz
----------------	------------------------

Service

DAkkS Certificate:	963-127
--------------------	---------

Category

Category:	Balances
Product Group:	Precision balance

Packaging & shipping

Delivery:	24 h
Dimensions packaging (WxDxH):	510 x 410 x 355 mm
Gross weight:	7,250 kg
Net weight:	4,950 kg
Shipping method:	Parcel service

Construction

Casing material:	Plastic
Dimensions draft shield (dxH):	160 70
Level indicator:	yes
Material weighing plate:	stainless steel
Overall dimensions mounted (WxDxH):	210 x 340 x 160 mm
Revolving screw feet:	yes
Weighing space (dxH):	150 60
Weighing surface (d):	110

Measuring system

Adjustment options:	Internal calibration (auto)
Linearity:	3 mg
Readout [d]:	1 mg
Reproducibility:	1 mg
Resolution:	1.200.000
Stabilisation time:	2 s
Tare range:	1,200 kg
Warm up time:	8 h
Weighing range [Max]:	1,200 kg
Weighing system:	Force compensation
Weighing units:	ct dwt g gn lb mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw)

Display

Display digit height:	1,700 cm
-----------------------	----------

Technical data about verification

n/a:	2 g
------	-----

Counting

Counting resolution:	240000
Minimum piece weight at piece counting:	5 mg
Reference weight:	yes