## KERN PLJ3000-2CM



Process reliability thanks to automatic internal adjustment and EC type approval [M]



## Measuring system

Adjustment options:	Internal calibration (auto)
Linearity:	40 mg
Readout [d]:	10 mg
Reproducibility:	10 mg
Resolution:	350000
Stabilisation time:	4 s
Tare range:	-3500000 mg
Warm up time:	2 h
Weighing range [Max]:	3,500 kg
Weighing system:	Force compensation
Weighing units:	ct g kg

1,700 cm

70000 50 mg

## Display

Display digit height:

## Technical data about verification

Minimum load [Min]:	500 mg
n/a:	20 g
Periodic Verification Italy:	969-112
Verification approval conforming to 90/384/EEC:	yes
Verification by KERN possible:	yes
Verification class:	II
Verification value [e]:	100 mg
Counting	

Counting resolution:	
Mininum piece weight at piece	
counting:	

Functions	
Counting function:	yes
Data hold function:	yes
Density determination function:	yes
Function to save totals:	yes
Peak function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
SLEEP function:	yes
Standby function:	yes
Statistical function:	yes
Suspended weighing:	Hook
Time display:	yes
Vibration-free weighing (Animal weighing program):	yes
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	40 °C
Minimum ambient temperature:	10 °C
Power supply	
Input voltage:	100 V - 240 V
	100 V - 240 V
Input voltage:	100 V - 240 V 963-127
Input voltage: Service	
Input voltage: Service DAkkS Certificate:	963-127
Input voltage: Service DAkkS Certificate: Verification:	963-127
Input voltage: Service DAkkS Certificate: Verification: Category	963-127 965-216
Input voltage: Service DAkkS Certificate: Verification: Category Category:	963-127 965-216 Balances
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping	963-127 965-216 Balances
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery:	963-127 965-216 Balances Precision balance 24 h
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg 4,800 kg
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg 4,800 kg Parcel service
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Dimensions housing (WÃDÃH):	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg 4,800 kg Parcel service 206 x 335 x 100 mm
Input voltage: Service DAkkS Certificate: Verification: Category Category Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Dimensions housing (WÃDÃH): Level indicator:	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg 4,800 kg Parcel service
Input voltage: Service DAkkS Certificate: Verification: Category Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Dimensions housing (WÃDÃH):	963-127 965-216 Balances Precision balance 24 h 480 x 380 x 340 mm 6,300 kg 4,800 kg Parcel service 206 x 335 x 100 mm