## KERN PLJ720-3A

Measuring system

Adjustment options:



Precision balance with user-friendly concept of operation, now also as milligram balance with an enormous weighing range up to 2100 g!

Internal calibration (auto)



mitorial cameration (acts)
2 mg
1 mg
1 mg
720000
2 s
720 g
4 h
720 g
Force compensation
ct dwt g gn lb mo oz ozt tl
(HK) tl (Singap. Malays) tl (Tw)
(HK) tl (Singap. Malays) tl
(HK) tl (Singap. Malays) tl
(HK) tl (Singap. Malays) tl (Tw)
(HK) tl (Singap. Malays) tl (Tw)
(HK) tl (Singap. Malays) tl (Tw) 1,700 cm
(HK) tl (Singap. Malays) tl (Tw) 1,700 cm
(HK) tl (Singap. Malays) tl (Tw)  1,700 cm

Functions	
Counting function:	yes
Density determination function:	yes
Peak function:	yes
Percentage determination:	yes
PRE-TARE function:	yes
Standby function:	yes
Suspended weighing:	Loop
Weighing with tolerance range:	yes
Environmental conditions	
Maximum humidity:	80 %
Maximum operating temperature:	35 °C
Minimum ambient temperature:	5°C
Power supply	
Input voltage:	220 V - 240 V AC 50 Hz
Service	
DAkkS Certificate:	963-127
Category	
Category Category:	Balances
	Balances Precision balance
Category:	
Category: Product Group:	
Category: Product Group: Packaging & shipping	Precision balance
Category: Product Group: Packaging & shipping Delivery:	Precision balance
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH):	Precision balance  24 h  500 x 360 x 420 mm
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight:	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction  Casing material:	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction  Casing material: Dimensions draft shield (dxH): Level indicator:	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service  Plastic  160   70
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction  Casing material: Dimensions draft shield (dxH):	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service  Plastic  160   70  yes
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction  Casing material: Dimensions draft shield (dxH): Level indicator: Material weighing plate: Overall dimensions mounted	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service  Plastic  160   70  yes  stainless steel
Category: Product Group:  Packaging & shipping  Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:  Construction  Casing material: Dimensions draft shield (dxH): Level indicator: Material weighing plate: Overall dimensions mounted (WxDxH):	Precision balance  24 h  500 x 360 x 420 mm  7,320 kg  4,900 kg  Parcel service  Plastic  160   70  yes  stainless steel  210 x 340 x 160 mm