

KERN RIB6K-3HM

High-quality retail scale with large item memory, user-friendly concept of operation and EC type approval [M]



Measuring system

| | |
|-------------------------------|----------------------|
| Adjustment options: | External calibration |
| Linearity: | 1 g 2 g |
| Readout [d]: | 1 g 2 g |
| Recommended adjusting weight: | 5 kg (F2); 1 kg (F2) |
| Reproducibility: | 1 g 2 g |
| Resolution: | 3 3.000 |
| Stabilisation time: | 2 s |
| Tare range: | 6 kg |
| Warm up time: | 10 min 10 min |
| Weighing range [Max]: | 3 kg 6 kg |
| Weighing system: | Strain gauge |
| Weighing units: | g kg |

Display

| | |
|------------------------------|----------|
| Additional Display possible: | yes |
| Display digit height: | 1,800 cm |

Technical data about verification

| | |
|---|-------------|
| Minimum load [Min]: | 20 g 40 g |
| Periodic Verification for Italy: | 969-112 |
| Verification approval conforming to 2014/31/EU: | yes |
| Verification by KERN possible: | yes |
| Verification class: | III |
| Verification value [e]: | 1 g 2 g |

Environmental conditions

| | |
|--------------------------------|--------|
| Maximum humidity: | 80 % |
| Maximum operating temperature: | 40 °C |
| Minimum ambient temperature: | -10 °C |
| Minimum humidity: | 0 % |

Power supply

| | |
|----------------|------------------------|
| Charging time: | 14 h |
| Input voltage: | 220 V - 240 V AC 50 Hz |
| n/a: | CH EURO UK |

| | |
|------|------------------------|
| n/a: | Mains adapter external |
|------|------------------------|

Power supply

| | |
|---------------------------------|----------------------------------|
| Operating time (Backlight off): | 80 h |
| Operating time (Backlight on): | 40 h |
| Rechargeable battery: | Rchrg. battery optional - intern |

Service

Adjustment at the location of installation: 961-248

| | |
|--------------------|---------|
| DAkkS Certificate: | 963-128 |
| Verification: | 965-228 |

Category

| | |
|----------------|-----------------------|
| Brand: | KERN |
| Category: | Balances |
| Product Group: | Price computing scale |

Packaging & shipping

| | |
|-------------------------------|--------------------|
| Delivery: | 24 h |
| Dimensions packaging (WxDxH): | 550 x 230 x 100 mm |
| Gross weight: | 4,800 kg |
| Net weight: | 3,800 kg |
| Shipping method: | Parcel service |

Construction

| | |
|-------------------------------------|--------------------|
| Casing material: | Plastic |
| Dimensions housing (WxDxH): | 325 x 400 x 400 mm |
| of stand: | 53 cm |
| Level indicator: | yes |
| Material weighing plate: | stainless steel |
| Overall dimensions mounted (WxDxH): | 325 x 400 x 400 mm |
| Revolving screw feet: | yes |
| Weighing surface (WxD): | 294 x 225 mm |